

SPECIFICATIONS

| Model Number | BCI Group | Voltage | 20 Hr Ah | Product Footnotes | Physical Specifications | | | | | | | | | |
|-------------------------------------|-----------|---------|-------------------|-------------------|-------------------------|------|------|-------------|-----|-----|--------------|-----|--------|------|
| | | | | | Inches | | | Millimeters | | | Term. Height | | Weight | |
| | | | | | L | W | H | L | W | H | in. | mm. | lbs. | kgs. |
| EMBASSY® AGM SERIES | | | | | | | | | | | | | | |
| 4CE4.5 | | 4 | 4.5 | T1 | 1.89 | 1.89 | 4.02 | 48 | 48 | 102 | 4.25 | 108 | 1.1 | 0.5 |
| 4CE10 | | 4 | 10.0 | T1 | 4.02 | 1.73 | 3.74 | 102 | 44 | 95 | 3.98 | 101 | 2.3 | 1.0 |
| 6CE1.2 | | 6 | 1.2 | T1 | 3.82 | 0.94 | 2.05 | 97 | 24 | 52 | 2.28 | 58 | 0.6 | 0.3 |
| 6CE3 | | 6 | 3.0 | T1 | 5.28 | 1.38 | 2.40 | 134 | 35 | 61 | 2.64 | 67 | 1.5 | 0.6 |
| 6CE5 | | 6 | 5.0 | T1 | 2.76 | 1.85 | 3.98 | 70 | 47 | 101 | 4.21 | 107 | 1.6 | 0.7 |
| 6CE7.5 | | 6 | 7.5 | T1 | 5.94 | 1.34 | 3.70 | 151 | 34 | 94 | 3.94 | 100 | 2.5 | 1.1 |
| 6CE8 | | 6 | 8.0 | T1 | 3.86 | 2.20 | 4.61 | 98 | 56 | 117 | 4.69 | 119 | 2.9 | 1.2 |
| 6CE12 | | 6 | 12.0 | T1, T2 | 5.94 | 1.97 | 3.70 | 151 | 50 | 94 | 3.94 | 100 | 4.2 | 1.8 |
| 6CE14 | | 6 | 14.0 | T3 | 4.25 | 2.80 | 5.51 | 108 | 71 | 140 | 5.51 | 140 | 5.2 | 2.2 |
| 6CE36 | | 6 | 36.0 | T2,B1 | 6.38 | 3.46 | 6.41 | 162 | 88 | 163 | 6.69 | 170 | 12.6 | 5.4 |
| 12CE1.2 | | 12 | 1.2 | T1 | 3.82 | 1.69 | 2.05 | 97 | 43 | 52 | 2.28 | 58 | 1.2 | 0.5 |
| 12CE2.3 | | 12 | 2.3 | T1 | 7.01 | 1.38 | 2.40 | 178 | 35 | 61 | 2.64 | 67 | 2.1 | 0.9 |
| 12CE3 | | 12 | 3.0 | T1 | 5.28 | 2.64 | 2.40 | 134 | 67 | 61 | 2.64 | 67 | 2.8 | 1.2 |
| 12CE5 | | 12 | 5.0 | T1 | 3.54 | 2.76 | 3.98 | 90 | 70 | 101 | 4.21 | 107 | 3.7 | 1.6 |
| 12CE7.5 | | 12 | 7.5 | T1,T2 | 5.94 | 2.56 | 3.70 | 151 | 65 | 94 | 3.94 | 100 | 4.8 | 2.1 |
| 12CE10 | Scooter | 12 | 10.0 | T2 | 5.95 | 2.56 | 4.37 | 151 | 65 | 111 | 4.60 | 117 | 6.4 | 2.7 |
| 12CE12 | | 12 | 12.0 | T1,T2 | 5.94 | 3.86 | 3.74 | 151 | 98 | 95 | 3.98 | 101 | 8.0 | 3.4 |
| 12CE18 | | 12 | 18.0 | B1,T2 | 7.13 | 3.03 | 6.57 | 181 | 77 | 167 | 6.57 | 167 | 11.6 | 5.0 |
| 12CE21 | | 12 | 21.0 | M5 | 7.13 | 3.03 | 6.57 | 181 | 77 | 167 | 6.57 | 167 | 13.9 | 6.0 |
| 12CE21 W/C | UPS | 12 | 21 Watts per cell | Recess | 3.54 | 2.76 | 3.98 | 90 | 70 | 101 | 3.98 | 101 | 4.0 | 1.7 |
| 12CE26 | | 12 | 26.0 | B1,T2 | 6.50 | 6.93 | 5.00 | 165 | 176 | 127 | 5.00 | 127 | 17.1 | 7.4 |
| 12CE35 | U1 | 12 | 35.0 | J,H | 7.68 | 5.12 | 6.10 | 195 | 130 | 155 | 7.09 | 180 | 22.3 | 9.6 |
| 12CE40 | | 12 | 40.0 | B2 | 7.76 | 6.50 | 6.73 | 198 | 165 | 171 | 6.73 | 171 | 28.6 | 12.3 |
| 12CE55 | 22NF | 12 | 55.0 | J | 9.02 | 5.43 | 8.19 | 229 | 138 | 208 | 9.06 | 230 | 36.7 | 15.8 |
| 12CE75 | 24 | 12 | 75.0 | J,M,H | 10.20 | 6.61 | 8.31 | 260 | 168 | 211 | 9.06 | 230 | 49.3 | 21.2 |
| 12CE100 | 27 | 12 | 100.0 | J,M,H | 12.09 | 6.65 | 8.31 | 307 | 169 | 211 | 9.17 | 233 | 60.0 | 25.9 |
| 12CE110 | 31 | 12 | 110.0 | M,H | 12.91 | 6.77 | 8.50 | 328 | 172 | 236 | 9.29 | 236 | 67.3 | 29.0 |
| EMBASSY® AGM MONOBLOC SERIES | | | | | | | | | | | | | | |
| CE704 | 0809-0010 | 4 | 5.0 | T2 | 3.81 | 2.13 | 3.02 | 97 | 54 | 77 | | | 1.46 | 0.66 |
| CE705 | 0859-0010 | 4 | 8.0 | T2 | 3.81 | 2.13 | 4.00 | 97 | 54 | 102 | | | 2.02 | 0.92 |
| CE706 | 0809-0012 | 6 | 5.0 | T2 | 5.48 | 2.13 | 3.02 | 139 | 54 | 77 | | | 2.16 | 0.98 |
| CE707 | 0859-0012 | 6 | 8.0 | T2 | 5.48 | 2.13 | 4.00 | 139 | 54 | 102 | | | 3.15 | 1.43 |
| CE708 | 0818-0012 | 6 | 2.5 | T1 | 4.48 | 1.81 | 2.75 | 114 | 46 | 70 | | | 1.15 | 0.52 |

Specifications are subject to change without notice.

Key

- | | |
|---|--|
| B1 = Nut & Bolt M5 | M5 = Inserted M5 Threaded Terminal |
| B2 = Nut & Bolt M6 | Recess = Recessed Positive T2, Recessed Negative T1 |
| H = Fitted with Handle | T1 = Quick Disconnect Tabs 0.187 in x 0.032 in |
| J = Heavy Duty Nut & Bolt | T2 = Quick Disconnect Tabs 0.250 in x 0.032 in |
| M = Threaded Stainless Steel Stud Terminal | T3 = Polarized Quick Disconnect Tabs |



1445 Majestic Drive
P.O. Box 990
Fremont, OH 43420-0990 USA
+1-419-334-7181
Fax +1-419-334-7124
www.crownbattery.com
sales@crownbattery.com